

HP-262

Bluetooth Printer



Secification

Printing Method	Direct Thermal line
Resolution	203DPI
Print Width	48mm
Printing Speed	60mm/s(max)
Position Sensor	Input buffer: 4K FLASH:60K
Command set	TSPL, ESC/POS
Media Sensor	TransmissiveSensor
Position Sensor	Reflective Sensor
Interface	USB+Bluetooth
Barcode	UPC-A, UPC-E, EAN(JAN)13, EAN(JAN)8, CODE39CODEBAR, ITF, CODE39, CODE128, QR CODE
Character set	GB18030 Chinese, Big5 Chinese, Korean KS5601
Character Size	ANK Font, Font A: 12x24dot, Font B: 9x 17dot Korean, Simplified & Traditional Chinese: 24x24dot
Graphic	Support monochromatic BMP files
Paper roll	Thermal Paper
Media width	58mm
Roll OD	Max. outside diameter: 30 mm
Paper Feeding	Top Feeding
Input	5VDC, 1A
Volume	1000mAh
Stand by	3 day
Dimension	92mm*80mm*48mm (H*W*H)
Weight	165g (With Battery)

[Notice] : Specification are subject to change without notice

@Line: Neung_II, thanya_2527

Tel: 097-265-3563 , 092-323-8181 For more information : www.code-soft.co.th

สำนักงาน : เลขที่ 929/18 ม.9 ซีน 2 ถ.สุขุมวิท 107 ด.สาโรงเหนือ อ.เมืองสมุทรปราการ จ.สมุทรปราการ 10270