

TCP-M156

Reliable and Flexible

The TCP-M156 is an ergonomic design POS Terminal. The low power consumption CPU with reliable and durable architecture design to provide better POS solution on the market. Quick access to the hard drive disk to help you reducing your service cost and time. This terminal can matched your desire of high value POS solution.



- Low-power consumption CPU, reliability and flexibility POS Terminal
- Various peripherals - VFD, Multiple Size of Second Display and MSR

TCP-M156

Specification

CPU	<i>Intel Celeron J1900 quad-core 2.0 GHz</i>	<i>i5-4210U dual-core 1.7GHz</i>
Colour	<i>Black</i>	
Memory	<i>4GB DDR3</i>	
Storage	<i>M100-128GB Dual Channel (SATA 3 Gbps x 1 + mSATA(3) x1)</i>	
Main Board	<i>Baytrail mother board</i>	
Display Touch	<i>15.6" TFT touch screen</i>	
Panel	<i>10 points capacitive touch panel</i>	
Resolution	<i>1366 x 768</i>	
Operating System	<i>Windows 7 / 8 / 10 / IoT 10</i>	

I/O Ports

USB 2.0	<i>6</i>	<i>4</i>
Serial Port	<i>1</i>	<i>-</i>
LAN Port	<i>1</i>	<i>1</i>
Ethernet	<i>Realek PCI-E NIC RTL 8111E for 1000M bps</i>	
Audio Port	<i>1</i>	<i>1</i>
Audio	<i>Realtek ALC662 5.1 Channel HDA Codec , Support MIC/Line-out Ports 1* Amplifier</i>	
VGA	<i>-</i>	<i>1</i>
HDMI	<i>-</i>	<i>1</i>

Peripheral

Camera, Built-in Peripheral

Operating Temperature *MSR, VFD, Second Display & WiFi*

0°C ~ 60°C

Storage Temperature *-10°C ~ 70°C*

Certificate *CE / ROHS / FCC*

Electrical

Power Supply Input / Output *AC 100V-240V, 50-60Hz, DC12V / 5A*

[Notice] : Specification are subject to change without notice