

TP-300K

Kitchen Thermal Receipt Printer

Fast, Reliable and Easy To Configure

The TP-300K is easy load and front-feeding access thermal printer. It is fast, reliable, easy to configure and supports all the leading mobile operating systems.

It features fast printing up to 300mm/second, built-in loudspeaker make big alarm sound after receipts printed, ideal for kitchen or others noisy environment with trusted reliability, is perfect for use in restaurant, kitchen and others noisy environment.



- ✓ Easy load and easy front-feeding access
- ✓ Interface: Serial+USB+Ethernet standard
- ✓ 300mm/sec high print speed
- ✓ Built-in loudspeaker (beeper after print)
- ✓ Front RED light tube design for status indication
- ✓ Support receipt detection and alarm function

TP-300K

Mechanical

Print Method	Direct thermal line
Printing Width	64mm or 76mm
Printing Speed	300mm/second
Auto Cutter	Full or Partial Cut
Dot Density	512dot/line or 576dot/line
Paper	79.5±0.5mm (width), 0.06~0.08mm (thickness), 83mm (roll diameter)
Interface	Serial+USB+Ethernet
Command	ESC/POS command
Character Size	ANK Font, Font A: 1.5x3.0mm (12x24dots), Font B: 1.1x2.1mm (9x17dots), Chinese Font
Data Buffer	128k bytes
Barcode Type	UPC-A /UPC-E /EAN13 /EAN8 /CODE39 /ITF /CODEBAR /CODE93 /CODE128 / QR Code
Operating Temperature	0°C to 45°C (operating); -10°C to 60°C (storage)
Print Head Life	100km
Cutter Life	1.5 million cuts
Weight	1.8kg

Electrical

Power Input	DC 24V/2.5A
Power Supply Input	AC 110V/220V, 50-60Hz
Cash Drawer Output	DC 24V/1A

[Notice] : Specification are subject to change without notice

*The instructions are all under the laboratorial measurements with specified paper.

For more information : www.code-soft.com

Code Soft International Information Co. Ltd.

Room 319, Block C, The NEW Generation Info Tech Park, Chuangye Road, No.139, Bao'An District, Shenzhen, P.R.China.