



Rich Interface

- Virtual serial port for USB connection
- USB+Serial+Ethernet
- Parallel+USB

HIGH PRINT SPEED (300mm/sec) INTEGRATED MECHANISM



Integration of mechanism and cutter

150km mechanism lifespan;
1,500,000 times cutter lifespan

TP-3300II Thermal Receipt Printer

INNOVATION, QUALITY

NEW PACKING, A NEW IMAGE



Specification

Print method	Direct thermal
Print speed	300mm/sec.
Paper width	79.5 ± 0.5mm
Print width	64/72mm
Interface	USB+Serial+Ethernet, Parallel+USB
Wall mount	Support
Power	DC24V/2A
Reliability	150km mechanism lifespan; 1,500,000 times cutter lifespan
Weight	1.23kg
Dimension	180.6X139X127MM(LXWXH)

NEW SIMPLE. BETTER. FASTER Thermal Receipt Printer



TP-3300II



Support 2D Barcode Printing
Integration of mechanism and cutter
300mm/sec ultra high speed

- ♦ Compatible with ESC/POS and Star commands
- ♦ Waterproof, oil-proof, dust-proof structure
- ♦ Kitchen printing and network printing supported
- ♦ Network status monitoring, multilink printing supported
- ♦ OPOS driver supported
- ♦ Printer authentication and software bundle

- ♦ High speed driver printing mode, serial port speed is 66% faster
- ♦ Auto print recovering when network disconnected
- ♦ Virtual serial port for USB connection, USB port supports OPOS application
- ♦ 100MB network interface card makes the connection and print much faster; stop receipts misprinting