
TP-3250IIL

Proficient Commercial POS Receipt Printer



- Both of Epson ESC/POS
 - 250mm/sec ultra high printing speed
 - Bar code printing
 - Paper width including 80mm
 - Support IP change by using Serial or USB port
 - All-in-one Serial, USB, 100M Ethernet interface
-



TP-3250IIL

Specification

Print Method	Thermal Line Printing
Print Width	80mm: 72mm / 567dots
Dot pitch	567dots / line 512dots / line
Printing speed	250mm/sec (60 lines / sec
Auto cutter	Full or Partial
Number of columns	80mm: Front A - 42 columns / 48 columns / Front B - 56 columns / 64 columns / Simplified / Traditional Chinese - 21 columns / 24 columns
Character Size	ANK Character, Front A : 1.5 x 3.0mm (12 x 24 dots) Font B: 1.1 x 2.1mm (9 x 17 dots) Simplified / Traditional Chinese : 3.0 x 3.0mm (24 x 24 dots
Character table	PC437 / Katakana / PC850 / PC860 / PC863 / PC865 WPC1252 / PC866 / PC852c / PC858 / Latvian / Arabic / PT151, 1251
Barcode Type	UPC-A/UPC-E/JAN-13/EAN-8/CODABAR/ITF/CODE39/CODE93/CODE128
Line spacing	3.75mm
Paper	79.5 +/- 0.5mm @ 83mm
Interface	USB + serial + Etherne
Input buffer	256K bytes
NV user memory	256K bytes
Drawer Kick-Out	DC 12-24V / 1A, 2 Drawer
Power Supply	DC 24V / 2.5A
AC adapter	Input: AC 110V / 220V, 50-60 Hz Output : DC 24V / 2.5A
Weight	1.30Kg
Operating	Temperature: 0-45 , Humidity: 10~80%
Storage	Temperature: 0-60 , Humidity: 10~90%

[Notice] : Specification are subject to change without notice



TP-3250IIL

Specification

Reliability	100KM
Driver	Win 9X / XP / NT / 2K / Vista / 7
Command	ESC / POS
Dimension (W*D*H)	145x 195 x 148mm
Safety	3C , CE

[Notice] : Specification are subject to change without notice